

+ IP
68

LOA

✓
3 YRS

Idt

FLX



PHYSICAL DATA

FEATURES

- RGB colourful strip
- 5050 LED with broader luminous surface
- Self-encapsulated design
- High quality PCB, high thermal 3M adhesive
- Widely adaptable to all types of controllers
- Double layer FPC(2oz) for good heat dissipation

MOUNTING

Surface

APPLICATION AREAS

Outdoor, Commercial, Residential, Retail, Hospitality

TECHNICAL DATA

LBLFLEXW14.4RGB


LAMP	SMD5050
OPERATING VOLTAGE-VAC	24V
TOTAL POWER (W)	14.4W
SYSTEM OUTPUT (LM)	620LM
EFFICACY (LM/W)	43
CCT (K)	42300K (All colours RGB @ 100%)
CRI (Ra)	50
BEAM ANGLE	120°
RATED LIFE (HRS)	50 000 HRS
CURRENT (MA)	0,6MA
OPERATING TEMP°C	-20°C TO 50°C
TC CASE MAX TEMP (°C)	60°C
MAC ADAM STEP	3 STEP
DIMENSIONS	5000mm x 12mm x 4mm
WEIGHT	0,35
CUT	100mm/cut



cd/klm

C0 - C180

C90 - C270



E&OE MAY OCCUR



Lights By Linea
Since (1990)

Cape Town | 48 Marine Dr, Paarden Eiland | T: +27 21 511 6116
info@lightsbylinea.com | www.lightsbylinea.com