

- + IP 20**
- 
- 5 YRS**
- LOA**
- ldt**

### PHYSICAL DATA

#### FEATURES

- Material: Aluminium frame with opal diffuser with iron backsheet
- Back-lit panel
- Isolated driver
- Non-flicker
- Surge protection >1000V
- Philips driver
- 3m Cabtyre with 5Amp Plugtop

#### OPTIONS & ACCESSORIES

- Surface mount frame B
- Suspension kits
- DALI Driver

#### MOUNTING

Recessed


#### APPLICATION AREAS

Indoor, Commercial, Retail, Hospitality

### TECHNICAL DATA

|                       | LLEDP1340              | LLEDP1341               | LLEDP1355               |
|-----------------------|------------------------|-------------------------|-------------------------|
| TOTAL POWER (W)       | 42W                    | 55W                     | 55W                     |
| SYSTEM OUTPUT (LM)    | 4200LM                 | 6050LM                  | 6050LM                  |
| EFFICACY (LM/W)       | 100                    | 110                     | 110                     |
| CCT (K)               | 3000 / 4000 / 6500K    | 3000 / 4000 / 6500K     | 3000 / 4000 / 6500K     |
| CRI (Ra)              | 80                     | 80                      | 80                      |
| UGR                   | ≤22                    | ≤22                     | ≤22                     |
| R9 VALUE              | >10                    | >10                     | >10                     |
| BEAM ANGLE            | 110°                   | 110°                    | 110°                    |
| OPERATING VOLTAGE-VAC | 220-240V               | 220-240V                | 220-240V                |
| OPERATING TEMP °C     | -20°C to 40°C          | -20°C to 40°C           | -20°C to 40°C           |
| CURRENT (MA)          | 1050MA                 | 1400MA                  | 1400                    |
| RATED LIFE (HRS)      | 50 000HRS              | 50 000HRS               | 50 000HRS               |
| POWER FACTOR          | >0.95                  | >0.95                   | >0.95                   |
| DIMENSIONS            | L:595 x W:595 x H:32mm | L:1195 x W:295 x H:32mm | L:1195 x W:595 x H:32mm |

- CD / KLM
- C0 - C180
  - C90 - C270



E&OE MAY OCCUR

