



+ IP  
66



✓  
5 YRS

ldt

### PHYSICAL DATA

#### FEATURES

- Material: Die-cast aluminium housing with UV-resistant polycarbonate lens
- LED Performance Highbay G4 is energy saving thanks to system efficacy
- Pre-wired with 500mm cable
- IK08 Impact rating (shock-resistance)
- Surge Protection L-N> 4000V, LN-G>6000V

#### MOUNTING

Suspended

#### APPLICATION AREAS

Indoor, Outdoor, Commercial, Retail, Hospitality

### TECHNICAL DATA

4058075726062

4058075726093

4058075726161

LAMP	LED	LED	LED
TOTAL POWER (W)	100W	150W	200W
SYSTEM OUTPUT (LM)	16000LM	24000LM	32000LM
EFFICACY (LM/W)	160	160	160
CCT (K)	4000K / 6500K	4000K / 6500K	4000K / 6500K
CRI (Ra)	80	80	80
BEAM ANGLE	90°	90°	60°
OPERATING VOLTAGE-VAC	100 - 277V	100 - 277V	100 - 277V
OPERATING TEMP °C	-30°C to +50°C	-30°C to +50°C	-30°C to +50°C
CURRENT (MA)	460MA	700MA	850MA
RATED LIFE (HRS)	50 000HRS@L80 (Ta=35°C) 100 000HRS@L80 (Ta=25°C)	50 000HRS@L80 (Ta=35°C) 100 000HRS@L80 (Ta=25°C)	50 000HRS@L80 (Ta=35°C) 100 000HRS@L80 (Ta=25°C)
POWER FACTOR	0.9	0.9	0.9
THD	≤10%@230V	≤10%@230V	≤10%@230V
IMPACT RATING	IK08	IK08	IK08
WEIGHT (KG)	2.2KG	2.2KG	2.865KG
DIMENSIONS	D:φ298 x H:117mm	D:φ298 x H:117mm	D:φ336 x H:119mm

