

- +IP 20**
-
- LOA**
-
- 5 YRS**
- ldt**

PHYSICAL DATA

FEATURES

- Material: Aluminum
- CCT selectable
- Dimming: On/off DALI
- Modular structure, easy for driver replacement
- Available in single and continuous linear
- Easy connection and maintenance
- Magnetic upright module
- Up & down light distribution ration can be adjusted

OPTIONS & ACCESSORIES

- Suspension accessories and extra 2.4m rollable diffuser
- Available in 3 lengths: 1200mm / 1500mm / 3000mm
- Direct lighting wattages: 30W / 40W / 80W
- Indirect lighting wattages: 40W / 50W / 100W

MOUNTING

Suspended and Surface mounted

APPLICATION AREAS


Indoor, Commercial, Banks, Schools, Offices, Retail

TECHNICAL DATA

LSL114CCT31

LAMP	LED
TOTAL POWER (W)	40W
SYSTEM OUTPUT (LM)	5200LM
EFFICACY (LM/W)	130LM/W
CCT (K)	3000K / 4000K / 5000K
CRI (Ra)	90
BEAM ANGLE	60° DOWN 120° UP
RATED LIFE (HRS)	50 000HRS L90B10
UGR	<19
MAC ADAM STEP	SDCM <3
DIMENSIONS	W:45 x L:1200 x H:75mm

- CD / KLM
- C0 - C180
 - C90 - C270



E&OE MAY OCCUR

